



		setup	She	er 🔽			
Name:		Date	8	Ev	ent:		
Track Indoor Ou	ıtdoor O Size: Sm	a ll O Medi	ium O L	arge O Tra	action: Low	O Med O	High 🔾
Surface: Smooth •	Bumpy O Rutted O	Type: Lo	ose/Loa	my O Hard	l Pack 🔿 Blu	e Groove 🕻	Clay O
Bumpsteer//Ackerm	an/Servo Saver/Ste	ering Stor	Co	ndition: D	usty O Dry	O Wet O M	luddy 🔾
	→ washers over		FRONT of VEH	ICLE		Shocks:	
washers over #	# washers under	•	B ¹ ¹ ²		OIL/	FRONT	REAR
washers under #	#	(stock) 03 4 (option)			BRAND:		
Front			Turns	6-	PISTON		
8 ⁴ ₃	UNI/CVD		from # c fully tight	of washers	SPRING		
8 ² ₁	733				REBOUND	%	%
		8	suspensi FRONT	ON: REAR	STD/EMUL/VENT		
1 4 5		RIDE HEIGHT	PRONT	NEAN	NOTES:		
8 6 A 1		CAMBER			Tür	es/Wheel	S:
		CASTER				FRONT	REAR
		SWEEP			BRAND/TREAD		
		-			COMPOUND		
	"A" Block (0° WITH CENTER DOT INSERT)	KICK UP			INSERT		
		ANTI-SQUAT			WHEEL		
(Sweep)		TOE (in/out)			NOTES:	~	
	"B" Block (10° WITH CENTER DOT INSERT)	SWAY BAR SHOCK LENGTH			_	ferential ©	
		(DROOP)	Dodby/W		FRONT	CENTER	REAR
(Kick Up) Rear E	mdk		Body/Wi	MGR		 quipment	•
	UNI/CVD	BODY MAKE			ENGINE/		<u> </u>
3	8 ^v	WING MAKE POSITION SETTINGS		INGS	PIPE: FUEL/	/	
A B C OFFSET		0 2 0 2			PLUG:	/	
					RX BATT: (steering) / (throttle/brake)		
Q^2	1mm 2mm	(3 4	3 4	SERVOS:	Duftrestructure	_
345	АВ	1 - REARWA		2 - FORWARD LOW	CLUTCH/SPUR:	Drivetrain: /	(teeth)
	0	3 - REARWA		4 - FORWARD HIGH		/	((teetii)
	DOWNFORCE SETTINGS			CLUTCH SHOES:			
					CLUTCH SPRINGS:	(front)	(rear)
	"C" Block	-0			BRAKE BIAS:	% /	%
	(2° WITH CENTER DOT INSERT)	3	•	(downforce angles)		nassis Brace	
(Anti-Squat)			Wheelba	ase:		eft O R Rear Short brace is always u	
	"D" Block	7A		mm <u>/FRONT</u>		Notes:	
(Rear Toe)	(3° WITH CENTER DOT INSERT)	large 2mm					
0° 5° 1° 6	5° 1° 1° 5° 5° 1°	small 1mm	-	mm <u>/REAR</u> ———			