TEKNO®	Setup She	eet E	B 4	<i>‡</i> 2.0
Name:	Date:		ent:	
		_		
Bumpsteer/Ackerman/Servo Saver/Sto				
	eening stop.	NT OF VEHICLE	FULL	
WASHERS:	(plate can be flipped)		TURNS FROM FULLY TIGHT	WASHERS:
Front End:	Suspensi	ion:		ntial Oil:
UNI/CVD	RIDE HEIGHT:	CAMBER:	/	/
	CASTER BLOCK:	SWEEP:	Drive	etrain:
OFFSET	KICK UP:	TOE:	PINION / SPUR:	(teeth)
	SWAY BAR:	DROOP:		oment:
	Shocks	5:	ESC: BATTERY:	
	OIL:	BRAND:	MOTOR:	
	PISTON:	SPRING:	SERVO:	
	REBOUND:	BUILD:	Chassi	s Braces:
			CENTER DIFF: O	REAR: O
(Arm Sweep)		B" Block: (Kick-Up)	BATTERY INNER: O	BATTERY OUTER: O
(0° with center dot inserts)	(10° wit	h center dot inserts)	Tires /	Wheels:
Rear End:	Suspensi	ion:	BRAND / TREAD:	
			COMPOUND:	
		CAMBER: TOE:	INSERT:	
		DROOP:	WHEEL: NOTES:	
			/ Wing:	
	Shocks	s:	BODY MAKE:	
		BRAND:	WING MAKE:	
		SPRING:	No	otes:
	REBOUND:	BUILD:		
	(D″ Block:		
"C" Block:	(2.5° wit	(Rear Toe) th center dot inserts)		
(Anti-Squat)	(2.5 Wit	center dot inserts/		
(1° with center dot inserts)	Rear Hub / Wheelbase:			
Arm Inserts:	ll Center)			
(Right Arm)	1 🜔 1(L+) Q	(Shims) (Thick - 2mm)		
		(Thick - 2mm) (Thin - 1mm)		
	а (M) С з(М) С			
ACTIVE TOE 0° 0° 1° out 1° out 1° in 1° in		REAR FRONT		