



Name:	Date:	Event:		Ambient Temp:				
Track: INDOOR •	outdoor Size: s	MALL O MEDIUM C	LARGE O	raction: Low O	MEDIUM 🤇) ніс	н О	
Surface: sмоотн	BUMPY O RUTTED O	Type: Loose/L	OAMY O HARD PACK	ED O BLUE GROOVE C	CLAY C	ASTR	O	
Ackerman/Bumpstee	r/Arm Plate/Spindle Heig	ıht/Servo Saver	Condition:	DUSTY O DRY O	WET O	MUDD	oy O	
		WASHERS:	<u> </u>	SPINDLE PART#			FULL	
	WASHERS: PLATE	A B C		TKR9141 (+1,0) TKR9141B (-1, -2)		F	URNS ROM ULLY	
	PLATE	W-32323333334	/ i i 🚐	TAR91410 (-1, -2)			IGHT	
Fron	t End:	Suspe	ension:	Differentials:				
A	UNI/CVD	RIDE HEIGHT:	CAMBER:	OPTION	FRONT	CENTER	REAR I	
	8 ⁰	CASTER BLOCK:	SWEEP:	Diff Oil D			<u> </u>	
	OFFSET	KICK UP:	TOE:	(TKR5144B)	0	0	0	
88	Omm 1mm		DROOP:	(TKR5144)	0	0	0	
	P ^{2mm}	Sho	ocks:	(TKR5145B)	0	0	0	
	Φ	OIL:	BRAND:	(TKR9145)				
		PISTON:	SPRING:	(1/(1/3)	0	0	0	
		REBOUND:	BUILD:	Standard (TKR9114-TKR9112)	, O	0	0	
(1)	A" Block:		"B" Block:	Lightened (TKR5114XB-TKR5112x)	0	0	0	
<u> </u>	TKR9161 (0mm)	 	TKR9162 (0mm)	MANA AND AND AND AND AND AND AND AND AND				
	TKR9161B (-1mm)		TKR9162B (-1mm)	(TKR9150)		O	0	
Real	r End:	Suspe	ension:	(TKR9150B)	0	0	0	
	UNI/CVD	RIDE HEIGHT:	CAMBER:	(TKR9115)	0	0	0	
	9 3 8 9 9 9 9 9 9 9 9 9 9	ANTI-SQUAT:	TOE:			0		
	REAR HUB OFFSET	SWAY BAR:	DROOP:	(TKR9115B)		U		
000	A Dom	m Sho	ocks:	(TKR9149)	0	0	0	
	1 2m		BRAND:	(TKR9149A)	0	0	0	
-00		PISTON:	SPRING:	Bulk	heads:			
	10	REBOUND:	BUILD:		FRONT	REAR	_	
		Chass	sis Braces:		(R9412 O		16 0	
	REAR HUB -2mm	REAR-SHORT:	REAR-LONG:	TRR (-2	9416B O	TKR941 (-2mm)) PB O	
888	0mm +2mm	Tires	/ Wheels:	Driv	etrain:			
666	"C" Block:	BRAND / TREAD:		CLUTCH / SPUR:		((teeth)	
Screw ○ → (TKR1324)	TKR9163B (-1mm)	COMPOUND:		CLUTCH SHOES/SPRINGS:	/			
(TATT524)	TKR9163C (-2mm)	INSERT:		BRAKE BIAS %:	(front)		(rear)	
	"D" Block:	WHEEL:			Engine/Electronics			
	TKR9164B (-1mm)		Body / Wing:		ENGINE / PIPE: / FUEL / PLUG: /			
	TKR9164C (-2mm)			STEERING THROTTLE / BRAKE				
Wheelbase:		WING MAKE:		SERVOS:				
Tee Susc.	(Shims)	WING MOUNT POSITION:			otes:			
	(Thick - 2mm)		mm: O + 12mm: O					
REAR FF	(Thin - 1mm)	NOTES:						

NOTES: