



Name: PRES II OC	Dat	Data		Events SC SHOWDOWN @ HODDYDLEY			
Name: PRES ILOG		Date:		Event: SC SHOWDOWN @ HOBBYPLEX			
Track Conditions: Outdoor Indoor Wet Dry High Bite Low Bite							
Rough Smooth Hard Packed X Loose/Loamy Blue Groove							
Bumpsteer/Ackerman/Servo Saver: #washers Shocks:							
# washers over		front middle rear			FRONT	REAR	
under # washers	der			OIL	30 LOSI	27.5 LOSI	
Front End:		real	6.00 _{mm}	PISTON	8 X 1.3	8 X 1.3	
		Suspension:		SPRING	PINK	GREY	
01		FRONT	REAR	REBOUND	0 %	0 %	
A B A B A B A B A B A B A B A B A B A B	RIDE HEIGHT	24MM	24MM	-	-	BLADDER/VENTED	
	CAMBER	-2	-2		res / Whee		
	TOE (in/out	2 OUT			FRONT	REAR	
	SWAY BAR	2.4MM	2.2MM	BRAND/TREAD	AKA SLINGSHOTS	AKA SLINGSHOTS	
	SHOCK LENGT (DROOP)	104MM	112MM	COMPOUND	SUPER SOFT	SUPER SOFT	
		Body/Mou		INSERT	AKA RED	AKA RED	
	BODY MAKE	LOSI SC	ΓE	WHEEL	AKA 23006	AKA 23006	
	0	Front (Height)		NOTES:			
				Di	ifferential	Oil:	
				FRONT	CENTER	REAR	
				PTRC 5K	6K	4K	
(Sweep) (Kick Up)				Electronics:			
				ESC: HOBBYWING			
Rear End:	0	Rear (Height)		Battery: THUNDERPOWER			
				Motor: HOBBYWING 4000KV			
	11111			Radio: KO PROPO			
8 ⁴	ВС			Servo: HITEC 7940			
				Drivetrain:			
94		Wheelbase:			SPUR GEAR Metal Composite X		
86		4 mm /FRONT 1 mm /REAR large 2mm			Traktion Drive 🔲 Elektri-Clutch 🔲 Pinion 🗵		
					PINION SIZE 18 (teeth)		
					Mechanical Brakes Motor Brakes		
					Chassis Braces:		
			small 1mm	Front X	Middle 🔲	Rear 🔲	
		Ner		(front bra	ace is always reco	mmended)	
Rear Outer Rear Inner	MEDIUM	Notes:					
		MEDIUM BITE/CHOPPY IN AREAS. 1976 GRAMS LESS BODY, BATTERY, TIRES.					
(Toe In) (Anti-Squat)	((。))	FULL TITANIUM/ALUMINUM SCREWS. FRONT SHOCK BODY, SPRINGS, AND TOWER USED ON REAR TO REDUCE WEIGHT. BATTERY TRAY MODDED AND FULL REAR.					